



Chapter:	4 - Technical Info	
Section:	Part 1 - Product Technical Specifications	
Page Title:	Tekno SuperStrip Collection - Tech Specs	
Page #:	1 of 3 - Chapter 4	November 2004

**Tekno SuperStrip Collection – Technical Specifications**

Technical Specifications for Tekno’s Rekord-Maxi Format

- **Product Name:**
  - Tekno Rekord-Maxi SuperStrip
- **Imported By:**
  - Wood Flooring International (WFI)  
Delran, NJ 856-764-2501  
e-mail: [info@teknona.com](mailto:info@teknona.com) – web: [www.teknona.com](http://www.teknona.com)
- **Thickness:**
  - 7/16” (11mm)
- **Face Width:**
  - 3-1/2” (90mm)
- **Length:**
  - Random Length - in a mix of lengths in 31”/35”/38” (78/88/98cm).
  - Packed in nested boxes of 25/27/28 sqft per box with 35” average length per.
- **Construction:**
  - Wear layer is a sawn, solid wood piece 1/8”+ thick (3.5mm).
  - Backing layer is a composite of 7 birch veneer plies, 1.1mm each, laminated together for a total thickness of 11/32” (7.5mm).
  - Back is cross scored to create a FlexBack for ease of installation.
- **Other Format Options:** From Italy by special order only, Tekno also offers:
  - **Rekord-Primo** - 3/8” x 2-5/8” x 22-1/8” long with a 4.5mm wear layer and a 5-ply backer. (10mm by 70mm by 580mm)
- **Grades** - Most species are available in 4 different grades:
  - Quartered (Straight Grain) Clear Grade - is a Clear Grade selected for straight graining and then further color sorted to disallow any pieces too dark or too light.
  - Clear Grade - is a defect free, color sorted grade, which includes both straight grain and flat sawn graining.
  - Select Grade - is similar to a Clear Grade except the percentage of flat sawn is typically higher and the color range slightly greater. It is still color sorted to disallow any pieces too dark or too light.
  - Natural Grade - compares to a low US select grade. Allows some minor character marks but no knots and wider range of color/grain variation than in Select Grade.
- **Moisture Content:**
  - 7.5% +/- 1.5%





Tekno NA Reference Manual		
Chapter:	4 - Technical Info	
Section:	Part 1 – Product Technical Specifications	
Page Title:	Tekno SuperStrip Collection - Tech Specs	
Page #:	2 of 3 - Chapter 4	November 2004

## Tekno SuperStrip Collection – Technical Specifications

### Specifications for Tekno’s Rekord-Maxi Format

■ **Specie Choices:**

Specie	Quartered Clear Grade	Clear Grade	Select Grade
<a href="#"><u>Cherry, Brazilian</u></a>		<b>X</b>	
<a href="#"><u>Chestnut, Patagonian</u></a>			<b>X</b>
<a href="#"><u>Doussie</u></a>			<b>X</b>
<a href="#"><u>Iroko/Kambala</u></a>			<b>X</b>
<a href="#"><u>Maple, N. American</u></a>		<b>X</b>	
<a href="#"><u>Oak, White*</u></a>	*rift & quartered select grade		
<a href="#"><u>Wenge</u></a>	<b>X</b>		<b>X</b>

**Other species available by Special Order from Italy.**

■ **Milling:**

- Milled w/TrueSquare edges and ends after pre-finishing with precise diamond tooling for absolutely square flush edges & end joints when installed.

■ **Finish:**

- Supplied pre-finished with a 9 coat, High Wear UV cured Acrylic Urethane w/aluminum oxide in base coats and Anti-Scratch top coats in a Matte Gloss.

■ **Shipping Weight:**

- Approx. 1.5 lbs. per sqft.

■ **Installation** - See WFI’s Tekno Installation Instructions before commencing installation. In brief:

- Where Tekno should not be installed:
  - Below grade w/o proper moisture barrier
  - On wet slabs or on wet wood subfloors without proper moisture barrier
- Installation Methods:
  - On wood subfloors, preferred method is glue down or may also be nailed/stapled.
  - Glue down on concrete slab or wood subfloor in which case:
    - use urethane mastic, (not a water based mastic), such as Bostick Best/Franklin 811+ on a properly prepared subfloor. Follow mastic manufacturer’s detailed installation instructions.
    - on concrete subfloor, install over sheet vinyl and follow vinyl manufacturer’s recommendations

■ **Do not** nail/glue this flooring to wet subfloors or in areas which will be subject to wet conditions !



## Tekno NA Reference Manual

Chapter:	4 - Technical Info	
Section:	Part 1 – Product Technical Specifications	
Page Title:	Tekno SuperStrip Collection - Tech Specs	
Page #:	3 of 3 - Chapter 4	November 2004

### Tekno SuperStrip Collection – Technical Specifications

#### Specifications for Tekno's Rekord-Maxi Format

- **Warranty Quick Review:** See WFI's Tekno Warranty for full details & all exclusions. Below is a brief overview of the main points in the warranty.
  - **Pre-Installation Guarantee** - Any visible milling/wood/grade/finish defects in excess of the industry standard 5% allowable will be replaced / credited by the manufacturer when set aside & returned prior to installation.
  - **Structural Guarantee:** Product will not delaminate - 25 year guarantee. (Exclusions - excessive moisture/soaking).
  - **Resanding/Refinishing Warranty** - this product may be re-sanded / refinished up to 3 times when performed correctly by a professional floor refinisher. (Exclusions - sanding excessive wear/gouges &/or improper sanding).
  - **Finish Guarantee** - for a period of 15 years residentially, the finish will not wear through to bare wood under normal conditions and with proper maintenance. (Exclusions - improper wear & tear, improper maintenance).
  
- **WFI's Web Site Links:** Below is a list of links to various relevant sections on Tekno North America's web site. Please be sure to visit our web site at [www.teknona.com](http://www.teknona.com) for complete information.
  - [www.teknona.com](http://www.teknona.com) - Tekno North America's web site.
  - [Tekno Engineered 2-Ply SuperStrip](#) - technical specifications for this flooring style.
  - [Tekno Marketing Aids / Sales Tools](#) - Tekno North America's Sample Store which offers all the marketing aids / sales tools available for the Tekno line.
  - [Tekno Individual Specie Sheets](#) - technical specifications for each specie and a list of all the formats & grades that specie is available in.
  - [Tekno Installation Instructions](#) - Tekno's Installation Instructions.
  - [Tekno Warranty](#) - for Tekno Product & Finish Warranties.
  - [Tekno's Maintenance Instructions](#) - for Tekno's Maintenance Recommendations.
  - [MSDS](#) - to access the Material Safety Data Sheets for this product & for Safety Recommendations.

Note: The links above are accessible when viewing on the web. If you are viewing this from a "hard copy" you can only access these links by visiting our web site at:

**[www.teknona.com](http://www.teknona.com)**